**RUST REMOVER** 

Page: 1

Compilation date: 02/07/2015

**Revision date:** 09/09/2016

Revision No: 2

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: RUST REMOVER

Product code: 556

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

### 1.3. Details of the supplier of the safety data sheet

Company name: Texatherm Systems Ltd

Centre House

Coker Road, Worle Industrial Estate

Weston Super Mare

**BS22 6BX** 

Tel: +44(0)1934 521155
Fax: +44(0)1934 521166
Email: info@texatherm.com

### 1.4. Emergency telephone number

**Emergency tel:** +44(0)1934 521155 (office hours only)

#### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1C: H314

Most important adverse effects: Causes severe skin burns and eye damage.

# 2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Hazard pictograms: GHS05: Corrosion



Signal words: Danger

Precautionary statements: P260: Do not breathe spray.

P280: Wear protective clothing/eye protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

### **RUST REMOVER**

Page: 2

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Haz. ingredients (label): OXALIC ACID DIHYDRATE; TARTARIC ACID 100%

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

#### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

### Hazardous ingredients:

OXALIC ACID DIHYDRATE - REACH registered number(s): 01-2119534576-33-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent		
205-634-3	6153-56-6	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Dam. 1: H318	1-10%		
TARTARIC ACID 100%						

		Eye Dam. 1: H318	
		Fire Dam. 4, 11240	
201-766-0 133	3-37-9 -	Skin Irrit. 2: H315; STOT SE 3: H335;	1-10%

#### Section 4: First aid measures

# 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10

minutes. If unconscious, check for breathing and apply artificial respiration if necessary.

If unconscious and breathing is OK, place in the recovery position. Transfer to hospital

as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Seek

medical attention if irritation persist.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

**Eye contact:** Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. There may be difficulty swallowing.

**Inhalation:** Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

**RUST REMOVER** 

Page: 3

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

#### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS.

Turn leaking containers leak-side up to prevent the escape of liquid.

## 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate

method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

# 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

#### 7.3. Specific end use(s)

Specific end use(s): No data available.

### Section 8: Exposure controls/personal protection

### 8.1. Control parameters

#### **RUST REMOVER**

Page: 4

### Hazardous ingredients:

#### **OXALIC ACID DIHYDRATE**

### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1 mg/m3	2 mg/m3	-	-

### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

#### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Impermeable gloves.

**Eye protection:** Tightly fitting safety goggles. **Skin protection:** Impermeable protective clothing.

### Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale yellow

Odour: Pleasant

Evaporation rate: No data available.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Viscosity: No data available.

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: No data available. Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

**Relative density:** 1.015 - 1.035 **pH:** 2

VOC g/l: No data available.

# 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

## 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

**RUST REMOVER** 

Page: 5

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## **Section 11: Toxicological information**

### 11.1. Information on toxicological effects

### **Hazardous ingredients:**

#### **OXALIC ACID DIHYDRATE**

ORL	RAT	LD50	1400	mg/kg
SCU	FRG	LDLO	757	mg/kg

# Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

#### Symptoms / routes of exposure

**Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

**Ingestion:** Corrosive burns may appear around the lips. There may be difficulty swallowing.

Inhalation: Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# Section 12: Ecological information

# 12.1. Toxicity

Ecotoxicity values: No data available.

### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

### **RUST REMOVER**

Page: 6

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

#### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Waste code number: 20 01 30

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

### **Section 14: Transport information**

**Transport class:** This product does not require a classification for transport.

# **Section 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

# 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

### **Section 16: Other information**

# Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

# **RUST REMOVER**

Page: 7

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.